

Data sheet

PT06505VBEN (Type 041), 5-pole

Page 1/6


P/N
31041105

2026/09/07


Illustrations



Dimensional drawing as an example



Drill pattern as an example



See enlarged drawings at the end of document

Product specification

- pin header, solderable
- centerline 5.00 mm, direction of connection vertical 0°
- open ends, guiding ribs
- color black



Data sheet

PT06505VBEN (Type 041), 5-pole

Page 2/6

P/N
31041105

2026/09/07

Technical Data

General Data

Solder pin length	3.35 mm		
pole size	5		
Insulating material class	CTI 600		
clearance/creepage dist.	3.7 mm		
Protection category	IP00		
Rated current	10 A		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Rated voltage	250 V	630 V	630 V
Rated test voltage	4 kV	4 kV	4 kV

Approvals

 V / A	300 / 15
approval UL - File No.	E121004
	250 V / 4 kV / 10 A / 1.0 mm

Material

insulating material	PA66
flammability class	V0
contact pin material	CuZnPb
contact pin surface	Ni + Ag
Glow-Wire Flammability GWFI	960 °C acc. to IEC 60695-2-12
Glow-Wire Flammability GWIT	775 °C acc. to IEC 60695-2-13

Climatic Data

upper limit temperature	105 °C
lower limit temperature	-40 °C

general

Tolerance	ISO 2768 -mH
Solderability	Acc. to JEDEC JESD22-B102E 245°C/5s

Application note

Data sheet

Page 3/6

PT06505VBEN (Type 041), 5-pole

**P/N
31041105**

2026/09/07

Technical Data

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.



Data sheet

Page 4/6

PT06505VBEN (Type 041), 5-pole

P/N
31041105

2026/09/07

Counterpart of

P/N	Designation
31007105	RP02505IBWC (Typ 007), 5-pole
31107105	RP02505HBWC Type 107
ASP0250504-002	SP02505HDNC ASP0250504-002

Data sheet
PT06505VBEN (Type 041), 5-pole


Page 5/6

P/N
31041105

2026/09/07

Illustrations

Dimensional drawing as an example



$L = (\text{pole size} - 1) \times \text{centerline} + 7.7 \text{ mm} [0.303]$



Data sheet
PT06505VBEN (Type 041), 5-pole

Page 6/6

P/N
31041105

2026/09/07

Illustrations

Drill pattern as an example

