
# Data sheet
## SP02506HDNC ASP025




**P/N**
**ASP0250604**

2026/11/09

## Illustrations



Dimensional drawing as an example




See enlarged drawings at the end of document

## Product specification

- spring clamp terminal block, pluggable
- centerline 5.00 mm, direction of connection 90°
- fittable without loss of poles
- color gray
- eccentric lever, wire entry perpendicular to plug direction

METZ CONNECT GmbH | Im Tal 2 | 78176 Blumberg | Germany
Phone +49 7702 533-0 | Fax +49 7702 533-433 | info@metz-connect.com
Weitere Dokumentation siehe / additional documentation see / documentation supplémentaire voir www.metz-connect.com

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

## Technical Data

| | | | |
|---|---|---|---|
| **General Data** | | | |
| pole size | 6 | | |
| Insulating material class | CTI 600 | | |
| clearance/creepage dist. | 3.7 mm | | |
| Protection category | IP20 | | |
| Insul. strip length | 4 mm | | |
| Rated current | 10 A | | |
| Overvoltage category | III | III | II |
| Pollution degree | 3 | 2 | 2 |
| Rated voltage | 40 V | 250 V | 250 V |
| Rated test voltage | 2.5 kV | 2.5 kV | 2.5 kV |
| **Terminal data** | | | |
| rat.wiring solid AWGmax | 0.08 mm² - 1.5 mm² / AWG 28 - AWG 16 | | |
| rat.wiring strand.AWGmax | 0.08 mm² - 0.75 mm² / AWG 28 - AWG 18 | | |
| **Approvals** | | | |
| c UL us V / A / AWG | 300 / 8 / 28 - 16 | | |
| approval UL - File No. | E121004 | | |
| SEV | 250 V / 4 kV / 10 A | | |
| **Material** | | | |
| insulating material | PA | | |
| flammability class | V0 | | |
| spring material | Spring steel | | |
| contact material | CuSn | | |
| Contact surface | Sn | | |
| Glow-Wire Flammability GWFI | 850 °C acc. to IEC 60695-2-12 | | |
| Glow-Wire Flammability GWIT | 775 °C acc. to IEC 60695-2-13 | | |
| **Climatic Data** | | | |
| upper limit temperature | 105 °C | | |
| lower limit temperature | -40 °C | | |
| **general** | | | |
| Tolerance | ISO 2768 -mH | | |

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

## Technical Data

### Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

## Accessories

| P/N | Designation |
|---|---|
| 720036-01-4 | Mounting flange gray for type ASP025 |
| 720036-02-2 | Mounting flange black for type ASP025 |

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!


## Counterpart

| P/N | Designation |
|---|---|
| 310171 | PR015xxVBHC Type 017 |
| 310391 | PT055xxHBHC Type 039 |
| 310411 | PT065xxVBEN Type 041 |
| 314171 | PM035xxVBHC (Type 417) |
| 3141710622 | PM03506VBHC (Type 417) |

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

## Illustrations

Dimensional drawing as an example




L=(pole size - 1) x centerline + 5 mm [0.197]

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!