

Data sheet

Page 1/2

FM20C04VBNN Buchsenleiste SMT lötbar 4 p einreihig vertikal 4,3mm hoch

FM20C04VBNN

2025/08/26

Product specification

- female connector, SMT solderable
- centerline 2.00 mm, direction of connection vertical 0°
- closed ends
- color black
- Tape & Reel packaging possible
- single row



METZ CONNECT GmbH | Im Tal 2 | 78176 Blumberg | Germany
Phone +49 7702 533-0 | Fax +49 7702 533-433

Weitere Dokumentation siehe / additional documentation see /
documentation supplémentaire voir www.metz-connect.com

Data sheet

Page 2/2

FM20C04VBNN Buchsenleiste SMT lötbar 4 p einreihig vertikal 4,3mm hoch
FM20C04VBNN

2025/08/26

Technical Data
General Data

pole size	4
Insulating material class	CTI 450
clearance/creepage dist.	0.65 mm
Protection category	IP00
Rated current	1 A

Material

insulating material	PA6
contact material	CuSn
Contact surface	Ni + Ag
contact pin material	CuSn
contact pin surface	Ni + Au Flash
Glow-Wire Flammability GWFI	-
Glow-Wire Flammability GWIT	-

Climatic Data

upper limit temperature	105 °C
lower limit temperature	-40 °C

general

Tolerance	ISO 2768 -mH
Solderability	reflowable

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).

