

Data sheet

FR20C04HBNN Buchsenleiste THR lötbar einreih

einreihig horizontal 4 polig P/N FR20C04HBNN

2025/08/26

Product specification

- female connector, THR solderable
- centerline 2.00 mm, direction of connection 90°
- closed ends
- · color black
- · Tape & Reel packaging possible
- · single row



Data sheet Page 2/2

FR20C04HBNN Buchsenleiste THR lötbar einreihig horizontal 4 polig P/N FR20C04HBNN

2025/08/26

Technical Data

| General Data | |
|-----------------------------|---------------|
| Solder pin length | 3 mm |
| pole size | 4 |
| Protection category | IP00 |
| Rated current | 1 A |
| Material | |
| insulating material | PE-HT |
| contact pin material | CuSn |
| contact pin surface | Ni + Au Flash |
| Glow-Wire Flammability GWFI | - |
| Glow-Wire Flammability GWIT | - |
| Climatic Data | |
| upper limit temperature | 105 °C |
| lower limit temperature | -40 °C |
| general | |
| Tolerance | ISO 2768 -mH |
| Solderability | reflowable |

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).



