

Data sheet

Page 1/2

FR20C04VBNN Buchsenleiste THR lötbar einreihig vertikal 4 polig P/N
FR20C04VBNN

2025/08/26

Product specification

- female connector, THR solderable
- centerline 2.00 mm, direction of connection vertical 0°
- closed ends
- color black
- Tape & Reel packaging possible
- single row



Data sheet

Page 2/2

FR20C04VBNN Buchsenleiste THR lötbar

einreihig vertikal 4 polig

P/N

FR20C04VBNN

2025/08/26

Technical Data

General Data

Solder pin length	2.2 mm
pole size	4
clearance/creepage dist.	0.65 mm
Protection category	IP00
Rated current	1 A

Material

insulating material	PE-HT
contact material	CuSn
Contact surface	Ni + Au
contact pin material	CuSn
contact pin surface	Ni + Au Flash
Glow-Wire Flammability GWFI	-
Glow-Wire Flammability GWIT	-

Climatic Data

upper limit temperature	105 °C
lower limit temperature	-40 °C

general

Tolerance	ISO 2768 -mH
Solderability	reflowable

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).

